

Safety Data Sheet



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: **RP7**

Recommended Use: Lubricating and penetrating spray which displaces water to help start wet engines, loosen nuts and bolts and release rusted locks.

Supplier: Selleys Australia, a division of DuluxGroup (Australia) Pty Ltd
ABN: 67 000 049 427
Street Address: 1 Gow Street,
Padstow, NSW 2211
Australia
Telephone Number: +61 2 9781 8777
Facsimile: +61 2 9781 8825
Emergency Telephone: **1 800 033 111 (ALL HOURS)**

2. HAZARDS IDENTIFICATION

This material is hazardous according to criteria of Safe Work Australia; HAZARDOUS SUBSTANCE.

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

Risk Phrases: Extremely Flammable. Harmful: May cause lung damage if swallowed.

Safety Phrases: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Poisons Schedule: None allocated.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
White spirit (Stoddard solvent)	8052-41-3	30-60%	R65
Butane	106-97-8	10-<30%	R12
Propane	74-98-6	10-<30%	R12
Ingredients determined not to be hazardous	-	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

Skin Contact:

If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

Safety Data Sheet

**Eye Contact:**

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.

Medical attention and special treatment:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Hazards from combustion products:

Flammable gas. On burning will emit toxic fumes.

Precautions for fire fighters and special protective equipment:

Heating can cause expansion or decomposition of the material, which can lead to the containers exploding. If safe to do so, remove containers from the path of fire. Keep containers cool with water spray. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Hazchem Code: 2YE

6. ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and clean up:

Shut off all possible sources of ignition. In the event of an aerosol can developing a leak, allow to fully discharge in the open air before disposal.

7. HANDLING AND STORAGE

Conditions for safe storage:

Store in cool place and out of direct sunlight. Store away from sources of heat or ignition. Store away from oxidising agents. Keep containers closed when not in use - check regularly for leaks.

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour, mists and aerosols. Ensure spray nozzle is always directed away from the user. May form flammable vapour mixtures with air. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke. Vapour may travel a considerable distance to source of ignition and flash back.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits: No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for constituent(s):

Butane: 8hr TWA = 1900 mg/m³ (800 ppm)

Propane: Asphyxiant

White spirits: 8hr TWA = 790 mg/m³

Safety Data Sheet



As published by the National Occupational Health and Safety Commission.

No Exposure Standards assigned to other constituents.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

Asphyxiant - gases which can lead to reduction of oxygen concentration by displacement or dilution. The minimum oxygen content in air should be 18% by volume under normal atmospheric pressure.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Use in well ventilated areas. Keep containers closed when not in use. An asphyxiant gas which can lead to the displacement or dilution of oxygen. The minimum oxygen content in air should be 18% by volume under normal atmospheric pressure.

Personal Protective Equipment:

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Selleys Factory Safe Handling Code: Green



MANUFACTURE, PACKAGING AND TRANSPORT: Green - Wear overalls (or 'issued' long pants and long sleeve tops), safety boots, gloves and safety glasses. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

For leaking aerosol cans: Blue - Wear overalls (or 'issued' long pants and long sleeve tops), safety boots, gloves and face shield or chemical goggles. If risk of inhalation exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

FOR CONSUMER USE: Use with adequate ventilation. No special personal protective equipment required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Aerosol
Odour:	Hydrocarbon
Solubility:	Insoluble in water.
Specific Gravity:	0.71 @20°C
Relative Vapour Density (air=1):	Not available
Vapour Pressure (20 °C):	Not available
Flash Point (°C):	Not available
Flammability Limits (%):	Not available
Autoignition Temperature (°C):	Not available
% Volatile by Weight:	84
Melting Point/Range (°C):	Not applicable
Boiling Point/Range (°C):	Not available
Decomposition Point (°C):	Not available
pH:	Not applicable
Viscosity:	Not applicable
Evaporation Rate:	Not available

10. STABILITY AND REACTIVITY

Chemical stability:	Stable under normal conditions of use.
Conditions to avoid:	Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition, and open flame.
Incompatible materials:	Incompatible with oxidising agents.
Hazardous decomposition products:	Oxides of carbon.
Hazardous reactions:	None known.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is showing signs of central system depression (like those of drunkenness) there is greater likelihood of the patient breathing in vomit and causing damage to the lungs.
Eye contact:	May be an eye irritant.
Skin contact:	Contact with skin may result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis.
Inhalation:	Breathing in vapour can result in headaches, dizziness, drowsiness, and possible nausea. Breathing in high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness. Intentional misuse by deliberately concentrating and breathing the contents can be harmful or fatal.

Safety Data Sheet



Long Term Effects:

No information available for the product.

Toxicological Data: No LD50 data available for the product.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Advise flammable nature. Do not puncture or burn can when empty; contents are under pressure. If aerosol can develops a leak, allow to fully discharge before disposal. Normally suitable for disposal at approved land waste site.

14. TRANSPORT INFORMATION

Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.



UN No: 1950
Class-primary 2.1 Flammable Gas
Proper Shipping Name: AEROSOLS
Hazchem Code: 2YE

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No: 1950
Class-primary: 2.1 Flammable Gas
Proper Shipping Name: AEROSOLS

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 1950
Class-primary: 2.1 Flammable Gas
Proper Shipping Name: AEROSOLS, FLAMMABLE

15. REGULATORY INFORMATION

Classification: This material is hazardous according to criteria of Safe Work Australia; HAZARDOUS SUBSTANCE.

Product Name: RP7
Substance No: 000703534601

Issued: 10/01/2012
Version: 4

Safety Data Sheet



Hazard Category: Xn: Harmful

Risk Phrase(s): R12: Extremely Flammable.
R65: Harmful: May cause lung damage if swallowed.

Safety Phrase(s): S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Poisons Schedule: None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

For further copies of this sheet or other product information contact Selleys Customer Service.

Phone: 1300 555 205 (Australia wide)
Fax: 1300 555 305 (Australia wide)
Phone: 0800 735 539 (New Zealand)
Fax: 0800 804 583 (New Zealand)

Reason(s) for Issue:

Change in Formulation

This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.